

PRELIMINARY AMENDMENT  
Serial Number: 09/932,647  
Filing Date: 17 August 2001  
Title: Host Control of Printer Ready  
Assignee: Lexmark International, Inc.

Page 2  
Docket: 2001-0099.01  
(LEX056)

### ***Listing of Claims:***

This listing of claims will replace all prior versions and listings of claims in the subject application.

1. (Cancelled)
2. (Cancelled)
3. (Previously Presented) The method as in claim 5 in which said predetermined signal comes from a host receiving page data scanned from scanned pages and said signal defines said predetermined time based in the time between said scanned pages.
4. (Cancelled)
5. (Currently Amended) A method of controlling a printer having a ready status and an on-but-not ready status and including a mirror having an operating speed comprising:  
determine a predetermined time interval that is less than the amount of time necessary for the mirror to coast from said operating speed to a full stop plus the amount of time necessary to accelerate from said full stop to said operating speed;  
starting a ready timer for the a predetermined time interval when a predetermined control signal is entered into said printer wherein said printer is in said ready status and said mirror is at said operating speed and executing one of the following:
  - (i) continuing said printer in said ready status when said timer does not reach said predetermined time interval; or
  - (ii) changing said printer to said on-but-not-ready status when said timer reaches said predetermined time interval, ~~wherein said predetermined time interval is less than the amount of time necessary for the mirror to slow from said operating speed to a stop and then return to said operating speed.~~

PRELIMINARY AMENDMENT  
Serial Number: 09/932,647  
Filing Date: 17 August 2001  
Title: Host Control of Printer Ready  
Assignee: Lexmark International, Inc.

Page 3  
Docket: 2001-0099.01  
(LEX056)

6. (Previously Presented) The method of claim 5, wherein said ready timer is started upon the completion of any print page.
7. (Previously Presented) The method of claim 6, further comprising resetting said ready timer.
8. (Previously Presented) The method of claim 5, wherein said predetermined control signal is entered into said printer when print data is delivered to a print engine in said printer.
9. (Currently Amended) A system for controlling a printer having a ready status and an on-but-not ready status comprising:
- a printer including a ready timer, a mirror having an operating speed and an automatic control apparatus; and
  - an input capable of entering a predetermined time interval and a predetermined control signal into said printer;
- wherein said automatic control apparatus is configured to:
- start said ready timer for a predetermined time interval when said predetermined control signal is entered into said printer wherein said printer is in said ready status and said mirror is at said operating speed, and execute one of the following:
- (i) continue said printer in said ready status until said timer reaches said predetermined time interval, or
  - (ii) change said printer to said on-but-not-ready status when said timer reaches said predetermined time interval, wherein said predetermined time interval is less than the amount of time necessary for the mirror to coast slow from said operating speed to a full stop plus the amount of time necessary to accelerate from said full stop and then return to said operating speed
10. (Previously Presented) The system of claim 9, wherein said automatic control apparatus is further configured to start said ready timer upon the completion of any print page.

PRELIMINARY AMENDMENT  
Serial Number: 09/932,647  
Filing Date: 17 August 2001  
Title: Host Control of Printer Ready  
Assignee: Lexmark International, Inc.

Page 4  
Docket: 2001-0099.01  
(LEX056)

11. (Previously Presented) The system as in claim 9, wherein said input comprises a host receiving page data scanned from scanned pages and said predetermined control signal defines said predetermined time interval based in the time between said scanned pages.
12. (Previously Presented) The system of claim 9, wherein said input is capable of entering said predetermined control signal when print data is delivered from said input to a print engine in said printer.
13. (Currently Amended) A printing apparatus having a ready status and an on-but-not ready status comprising:
- a ready timer,
  - a mirror having an operating speed and
  - an automatic control apparatus;
- wherein said automatic control apparatus is configured to:
- start said ready timer for a predetermined time interval wherein said printer is in said ready status and said mirror is at said operating speed, and execute one of the following:
- (i) continue said printer in said ready status until said timer reaches said predetermined time interval, or
  - (ii) change said printer to said on-but-not-ready status when said timer reaches said predetermined time interval, wherein said predetermined time interval is less than the amount of time necessary for the mirror to coast slow from said operating speed to a full stop plus the amount of time necessary to accelerate from said full stop and then return to said operating speed.
14. (Previously Presented) The printing apparatus of claim 13, wherein said automatic control apparatus is further configured to start said ready timer upon the completion of any print page.

**PRELIMINARY AMENDMENT**

Serial Number: 09/932,647

Filing Date: 17 August 2001

Title: Host Control of Printer Ready

Assignee: Lexmark International, Inc.

Page 5

Docket: 2001-0099.01

(LEX056)

- 
15. (Previously Presented) The printing apparatus of claim 13, including an input comprising a host receiving page data scanned from scanned pages and a predetermined control signal defines said predetermined time interval based in the time between said scanned pages.
16. (Previously Presented) The printing apparatus of claim 15, wherein said input is capable of entering said predetermined control signal when print data is delivered from said input to a print engine in said printer.
17. (Previously Presented) The printing apparatus of claim 13, wherein said automatic control apparatus comprises a microprocessor.